

OA200



RFID & Fingerprint Time Attendance & Access Control

BASE OA200 is developed with the concept of enhanced Fingerprint System. It is the combination of years' experience, high-tech R&D team's hard work and our understanding of global market. We are proud to consider it to be the most suitable model for global market of time attendance and access control system due to its multifunction, competitive price and graceful design full with sense of high technology. Its great performance is the excellent representative of our products. It will be your best choice of T&A and access control solution for companies, offices and governments.

FEATURES

World leading brand. Korean industrial design. Blue LCD. Super Slim Design.

Korean Optical fingerprint reader, Scratch-proof, Unbreakable and durable. Will accept all kinds of fingerprints.

Improved core module. 32 bit embedded Arm system. Super dual processor. High performance and Reliability..

Stand-alone without being connected with computer. Standard fingerprint capacity 2000.

Standard record capacity 50000.

Multiple identification method: Fingerprint only, card only, card + fingerprint, PIN+FP

Support user name display. 16 customizable time attendance status. Multimedia voice prompt.

Standard RS232/485 and TCP/IP communication. Wiegand26 and dry contact output.

Optional AMJ601 or AMJ602 access controller for separate type secure access control system.

Support real-time record download and WEB online tracking function.

Suitable for all kinds of complicated time attendance management. Easy-to-use and user-friendly software.

Item	Description
Sensor	Optical Sensor
LCD	Blue LCD
Identification Method	FP, ID+PW, CARD, CARD+FP, CARD+PW
Identification Time	≤1 second
Register Method	Finger, Password, ID card (Optional)
Scan Area	15mm*16mm
Resolution	500DPI
Fingerprint Capacity	2000/5000 (Optional)
Record Capacity	50000/150000 (Optional)
FRR	0.001%
FAR	0.00001%
Standard Port	RS232/485, TCP/IP, Wiegand26
Working Current	300mA
Sleeping Current	<20uA
ESD Tolerance	>15000V
Power	DC12V
Temperature/Humidity	-10deg C to <60deg C >/20%— 80%
Casing material	ABS industrial plastic
Size	140(w)×190(h)×30(d)mm
Color	Silver, Black (customizable)

SETTINGS

